

Technical Data Sheet

Date: 01-October-2024

Product Code: FL6000

ULTIMATE 2K HS Clearcoat Aerosol

RFU High Solids Express Clearcoat, specially formulated to allow easy application and good vertical holdup. Final Systems ULTIMATE 2K HS Clearcoat when cured, gives good depth of gloss to the final finish.

No hardener required, perfect for SMART and spot painting/repairs.

Gloss Levels: Gloss, Satin and Matt.

RFU = Ready for Use

Preparation

Ensure the surface is thoroughly clean, dry and free from dust, grease, oil or millscale etc before application.

Application



Health and safety "For professional use only"

Important: When using any new product, consult the "Health and Safety" data sheet. Always read the risks and precautions stated on the product label.



Shake can well before use 2 – 3 minutes

| | Apply 15 – 20cm away from panel Apply 2 coats Do not overload product onto panel. Do not apply more than recommended number of coats. This will cause product to not dry. |
|-----|---|
| (1) | Drying Times Flash Off 10 minutes between coats (ensure previous coat is dry) Fully Dried within 24 hours at 20°C Low heat may be used (This can be infrared at a safe distance) |
| | After use After use, turn the aerosol upside down and spray until the valve is clear; this will help prevent clogging. |

Technical Information

12 month shelf life when correctly stored in closed original container.

| Colour | Colourless |
|-------------|-----------------------|
| Gloss Level | Gloss, Satin and Matt |
| Flash Point | 22 - 30°C |
| VOC (EC) | 51.2% |
| Pack Size | 400ml Aerosol Can |

Health & Safety

Refer to relevant Health & Safety or Material Safety Data Sheets.

The technical data contained herein is based on our present knowledge and experience. We cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of the product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

