

## Technical Data Sheet

Date: 01-July-2024

Product Code: FL6002

### ULTIMATE Plastic Primer Aerosol

1K RFU high-performance Plastic Primer designed to prime plastic surfaces, making them ready for primers, topcoats, adhesives and sealants. Easy to use, fast drying and designed to provide exceptional adhesion to a wide variety of plastic substrates without the need for sanding.



Ideal for automotive refinishing and industrial applications. ULTIMATE Plastic Primer can be applied on many plastic substrates including: AAS, PC/PET, PETP, PP-E, PP+E/P, PP/EPDM and TSOP.





RFU = Ready for Use

#### Preparation

Ensure the surface is prepared with P240 - P320 grit and thoroughly cleaned, dry and free from dust, grease, oil or millscale etc before application.

#### Application

	<p>Health and safety "For professional use only"</p> <p>Important: When using any new product, consult the "Health and Safety" data sheet. Always read the risks and precautions stated on the product label.</p>
	<p>Shake can well before use 2 - 3 minutes</p>

	<p>Temperature</p> <p>To aid adhesion, make sure plastic is warm but not hot.</p>
	<p>Apply 15 - 20cm away from panel Apply 1 - 2 coats, dependant on type of plastic</p> <p><u>Do not</u> overload product onto panel. This causes lack of adhesion.</p>
	<p>Drying Times</p> <p>Flash Off 5 minutes Recoat after 15 minutes at 20°C</p> <p>Do not force dry Plastic Primer. Do not leave for more than 1 hour before overcoating or Plastic Primer will need scotching.</p>
	<p>After use</p> <p>After use, turn the aerosol upside down and spray until the valve is clear; this will help prevent clogging.</p>

## Technical Information

12 month shelf life when correctly stored in closed original container.

Relative Density	0.74 ± 0.01
Colour	Colourless
Flash Point	22 - 30°C
VOC (EC)	97.29%

## Health & Safety

Refer to relevant Health & Safety or Material Safety Data Sheets.

The technical data contained herein is based on our present knowledge and experience. We cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of the product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

