Printing date 29.03.2015

Revision: 29.03.2015

Product	identifier
Relevan No furth	ame: <u>Kapci 610</u> t identified uses of the substance or mixture and uses advised against er relevant information available. ion of the substance / the mixture 1263
Details o Manufa Kapci Co Industrio Port Said EGYPT	of the supplier of the safety data sheet cturer/Supplier: patings al Zone El - Raswa
	<i>information obtainable from: Product safety department</i> <i>ncy telephone number: During normal opening times:</i> +20 66 3770000
Hazara	Is identification
	ation of the substance or mixture ation according to Regulation (EC) No 1272/2008
Clussific	
	GHS02 flame
Flam. Li	q. 3 H226 Flammable liquid and vapour.
T	GHS05 corrosion
Eye Dan	n. 1 H318 Causes serious eye damage.
	GHS07
Skin Irri	t. 2 H315 Causes skin irritation.
STOT SI	E 3 H336 May cause drowsiness or dizziness.
<u>Classific</u>	ation according to Directive 67/548/EEC or Directive 1999/45/EC
Xn Xn	; Harmful
R20/21:	Harmful by inhalation and in contact with skin.
X Xi;	Irritant
R36/38:	Irritating to eyes and skin.
R10:	Flammable.
The prod preparat	tion concerning particular hazards for human and environment: duct has to be labelled due to the calculation procedure of the "General Classification guideling tions of the EU" in the latest valid version. Tation system:
	sification is according to the latest editions of the EU-lists, and extended by company and litera
Label el	
1 ahellin	g according to Regulation (EC) No 1272/2008

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 610

· Hazard pict	(Contd. of page 1)
GHS02	GHS05 GHS07
· Signal word	Danger
· Hazard-dete	ermining components of labelling:
butanol	
n-butyl acet	ate
Hazard stat	ements
H226 Flam	nable liquid and vapour.
H315 Cause	es skin irritation.
H318 Cause	es serious eye damage.
H336 May c	ause drowsiness or dizziness.
Precautiona	iry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P303+P361	+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
	with water/shower.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazar	
Deservites of D	

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB**: Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 1330-20-7	xylene	25-50%
EINECS: 215-535-7	Xn R20/21; Xi R38 R10	
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 123-86-4	n-butyl acetate	20-35%
EINECS: 204-658-1		
	🚸 Flam. Liq. 3, H226; 🜗 STOT SE 3, H336	
CAS: 84540-57-8	methoxypropyl acetate	2-12%
EINECS: 283-152-2	R10	
CAS: 78-83-1	butanol	2-12%
EINECS: 201-148-0	🗙 Xi R37/38-41	
	<u>R1</u> 0-67	
	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	
	(Co	ntd. on page

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 610

(Contd. of page 2)

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. • Information about fire - and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

Printing date 29.03.2015

Revision: 29.03.2015

(Contd. of page 3)

Trade name: Kapci 610

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

```
· Control parameters
```

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7	' xylene
-----------	----------

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

(Contd. on page 5)

GB

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 610

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

\cdot Eye protection:



Tightly sealed goggles

Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	108 °C	
Flash point:	24 °C	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	333 °C	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.	
Explosion limits:		
Lower:	1.1 Vol %	
Upper:	7.5 Vol %	
Vapour pressure at 20 °C:	10.7 hPa	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	84.0 %	

GB

Printing date 29.03.2015

Revision: 29.03.2015

(Contd. of page 5)

Trade name: Kapci 610

VOC (EC)

84.00 %

Solids content: • Other information 9.0 % No further relevant information available.

10 Stability and reactivity

· Reactivity

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 610

(Contd. of page 6)

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number ADR, IMDG, IATA	UN1263
	011203
UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
• Transport hazard class(es)	
ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADR, IMDG, IATA	111
· Environmental hazards:	
• Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
Danger coae (Kemier): EMS Number:	50 F-E,S-E
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
1 ···· 1 ·····························	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: El
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN1263, PAINT, 3, III

(Contd. on page 8)

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 610

(Contd. of page 7)

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R37/38 Irritating to respiratory system and skin.

R38 Irritating to skin.

- *R41 Risk of serious damage to eyes.*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- *R67 Vapours may cause drowsiness and dizziness.*

· Department issuing MSDS: Product safety department

· Contact: Mr. Rashad

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
- STOT SE 3: Specific target organ toxicity Single exposure, Hazard Category 3